

		Model								
		Anyvib 600-5	Anyvib 600-10	Anyvib 600-15	Anyvib 1200-5	Anyvib 1200-10	Anyvib 1200-15	Anyvib 2200-5	Anyvib 2200-10	Anyvib 2200-15
<b>F</b> <b>e</b> <b>a</b> <b>t</b> <b>u</b> <b>r</b> <b>e</b> <b>s</b>	Useful capacity	610	610	610	1120	1120	1120	2187	2187	2187
	Int. dimensions (mm) approx.									
	W	850	850	850	1000	1000	1000	1350	1350	1350
	D	740	740	740	1130	1130	1130	1350	1350	1350
	H	970	970	970	1080	1080	1080	1200	1200	1200
	External dimensions (mm)									
	W	1600	1600	1600	1600	1600	2050	2050	2050	2050
	D	2900	3100	3100	3550	3550	3550	4050	4050	4050
	H	2350*	2350*	2350*	2350**	2350**	2350**	2470**	2470**	2470**
	Temp. Range (°C)	-75° /+180°	-75° /+180°	-75° /+180°	-75° /+180°	-75° /+180°	-75° /+180°	-75° /+180°	-75° /+180°	-75° /+180°
	Temp. Accuracy (in time)	±0.1°C... ±0.8°C	±0.1°C... ±0.8°C	±0.1°C... ±0.8°C	±0.1°C... ±0.8°C	±0.1°C... ±0.8°C	±0.1°C... ±0.8°C	±0.1°C... ±0.8°C	±0.1°C... ±0.8°C	±0.1°C... ±0.8°C
	<u>Heating and cooling speed from -70°C to +180°C and viceversa**</u> *	5°C/min	10°C/min	15°C/min	5°C/min	10°C/min	15°C/min	5°C/min	10°C/min	15°C/min
RH range in the range +5/ +95°C	From 10% to 98%	From 10% to 98%	From 10% to 98%	From 10% to 98%	From 10% to 98%	From 10% to 98%	From 10% to 98%	From 10% to 98%	From 10% to 98%	
Electrical Power (kW)	25 (average 15)	35 (average 20)	42 (average 25)	35 (average 20)	48 (average 30)	68 (average 42)	43 (average 28)	74 (average 44)	98 (average 58)	
<u>Noise (dba)****</u>	70	72	74	72	74	80	74	80	84	
Weight (Kg)	1300	1700	2000	1900	2200	2700	2500	2900	3400	

\*add 600 mm for the highest position of the test cabinet

\*\*add 700 mm for the highest position of the test cabinet

\*\*\* average values without any internal load with ambient T +20/+22°C (according to IEC 60068-3-5)

\*\*\*\* measured at 1 meter from the front in a non reverberating room